

Model	DW-1.2-8	DW-1.2-10	DW-1.6-8	DW-1.6-10	DW-2-8	DW-2-10	
Quantity of unit	4	5	4	5	4	5	
Width of belt(m)	1.2		1.6		2		
Length of dry section (m)	8	10	8	10	8	10	
Thickness of raw material spreading (mm)	10-80						
Operation temperature (°C)	50~120						
Steam pressure (Mpa)	0.2~0.5						
Steam consumption (kg/h)	120-130	150-375	150-375	170-470	180-500	225-600	
Area of heat exchange (m <sup>2</sup> )	272	340	352	440	448	560	
Dry time (h)	0.2-1.2	0.25-1.5	0.2-1.2	0.25-1.5	0.2-1.2	0.25-1.5	
Dry capacity (kg water/h)	60-160	80-220	75-220	95-250	100-260	120-300	
Quantity of fan	5	6	5	6	5	6	
Total equipped power inside (kw)	9.9	12.1	9.9	12.1	18.2	22.2	
Total equipped power (kw)	11.4	13.6	11.4	13.6	19.7	23.7	
Overall dimensions	L (m)	9.77	11.77	9.77	11.77	9.77	11.77
	W (m)	1.5	1.5	2.24	2.24	2.66	2.66
	H (m)	2.83	2.83	2.83	2.83	3.50	3.50
Weight (kg)	4800	5780	5400	6550	6350	7800	